

## Container specifications/dimensions for the operated fleet

atualizado em 2018.01.30

	Container Types		Door openings		Internal Dimensions			Internal Capacity	Ratings		
	Type	Description	Width (m)	Height (m)	Length (m)	Width (m)	Height (m)	m3	Payload (Kg)	Gross Weight (Kg)	Tare (Kg)
20'	BK	Bulk	N/A	N/A	5,900	2,340	2,330	32,1	31 870	35 000	3 130
	DV	Dry Van	2,340	2,280	5,898	2,352	2,393	33,2	28 230	30 480	2 250
	SC	Palletwide	2,404	2,280	5,898	2,418	2,393	34,0	27 790	30 480	2 690
	SH	Dry High Cube/Palletwide	2,404	2,585	5,922	2,418	2,698	38,5	27 920	30 480	2 560
	OS	Open Side	N/A	N/A	5,890	2,280	2,250	30,4	22 250	25 400	3 150
	OT	Open Top	2,340	2,280	5,898	2,352	2,348	32,4	28 280	30 480	2 200
	PL/FL	Platform/Flat rack	N/A	N/A	5,632	2,226	2,233	N/A	31 200	34 000	2 800
	RF	Normal Reefer	2,290	2,264	5,450	2,294	2,273	27,0	27 560	30 480	2 940
	RH	Reefer High Cube	2,290	2,585	5,450	2,294	2,698	32,3	27 490	30 480	2 560
40'	DV	Dry Van	2,340	2,280	12,032	2,340	2,390	67,0	28 840	32 500	3 660
	HC	Dry High Cube	2,340	2,585	12,032	2,352	2,698	76,0	28 600	32 500	3 900
	SH	Dry High Cube/Palletwide	2,396	2,584	12,095	2,422	2,692	78,5	29 600	34 000	4 400
	OT	Open Top	2,340	2,280	12,032	2,352	2,348	66,4	2 862	32 500	3 880
	PL/FL	Platform/Flat rack	N/A	N/A	11,652	2,374	1,959	N/A	47 400	52 500	5 100
	CC4	Flat Car	N/A	N/A	12,095	2,422	N/A	N/A	9 000	16 250	7 250
	RF	Normal Reefer	2,290	2,298	11,563	2,290	2,218	58,0	28 550	32 480	3 930
	RH	Reefer High Cube	2,290	2,569	11,590	2,294	2,554	67,5	30 470	35 000	4 560